

# MATERIAL SAFETY DATA SHEET

PAGE 1

## SECTION 1 – PRODUCT INFORMATION

Blackfast Chemicals <i>Manufacturers name</i>	++44(0)20 83397370 <i>Telephone number</i>
Unit #5, Russell House, Molesey Road, Walton-on-Thames, Surrey, United Kingdom KT12 3PE	
Product identification : <b>BLACKFAST 933 WATER SOLUBLE OIL / CORROSION PREVENTATIVE</b>	Product identification # 933-25L, 933-4PK, 933-5L, 933-25LU, 933-4PKU, 933-5LU
Product use: <b>Rust preventative and water displacement</b>	Size: 25 litre, 4 pack, 5 litre
Suppliers name: <b>e-Black Solutions</b>	Emergency #: <b>1-866-878-8886</b>
Address: <b>13 Whitehall Lane, Cambridge, Ontario, Canada N1R 8N3</b>	

## SECTION 2 – HAZARDOUS INGREDIENTS

HAZARDOUS INGREDIENTS	%	CAS NUMBER	LD50 OF INGREDIENT
5-Chloro-2-methyl-2H-isothiazol-3-one	<0.02%	26172-55-4	Expected oral rat >2g/Kg
2-Methyl-2H-isothiazol-3-one N-(hydroxymethyl) formamide	<0.1%	2682-20-4	Expected dermal rabbit >2g/Kg

## SECTION 3 – PHYSICAL DATA

Liquid <i>Physical state</i>	Mild Odored Clear brown liquid <i>Odor and appearance</i>	Not Determined <i>Odor threshold</i>		
< 0.1 <i>Vapor pressure</i>	NE <i>Vapor density</i>	< 1.0 ( Water = 1 ) <i>Evaporation rate</i>	Not Determined <i>Boiling point</i>	< 0° C. <i>Freezing Point</i>
9.2 <i>pH</i>	NE <i>Specific Gravity</i>		NE <i>Solubility / Miscibility in water</i>	

## SECTION 4 – FIRE OR EXPLOSION HAZARD

<i>Conditions of Flammability: Flammable</i>			
<i>Means of extinction: CO2, dry powder, foam or water fog - DO NOT USE WATER</i>			
Above 150°C <i>Flash point and method</i>	6.5 <i>Upper flammable limit</i>	0.6 <i>Lower flammable limit</i>	
Above 230°C <i>Auto-ignition temperature</i>	NA <i>Hazardous combustion products</i>		
<i>Explosion Data:</i>	<i>Sensitivity to mechanical impact:</i> NONE	<i>Sensitivity to static discharge:</i> NONE	

## SECTION 5 – REACTIVITY DATA

<i>Chemical stability: Stable at normal temperatures &amp; under normal conditions.</i>
<i>Incompatibility with other substances: Avoid strong oxidizing agents. ( Strong Acids or Alkalines )</i>
<i>Reactivity and under what conditions?: NA</i>
<i>Hazardous decomposition products: NA</i>

## SECTION 6 – HEALTH HAZARD DATA (TOXICOLOGICAL PROPERTIES)

<i>Route of entry: Skin contact, eye contact, inhalation and ingestion.</i>	
<i>Effects of acute exposure to the product:</i>	May cause dizziness, headache, or vomiting
<i>SKIN:</i> Defats the skin. May cause irritation.	<i>EYES:</i> Causes irritation. Vapor may cause irritation.
<i>INHALATION:</i> Mist and vapors may cause irritation to nose and respiratory tract. Vapors may cause headaches, dizziness and central nervous system depression. Long term vapor inhalation can cause kidney damage.	
<i>INGESTION:</i> May cause nausea, vomiting and diarrhea. Aspiration of liquid during ingestion or vomiting may cause severe chemical pneumonitis. May cause lung damage if swallowed.	

Continued to page 2

SECTION 6 – HEALTH HAZARD DATA (TOXICOLOGICAL PROPERTIES) – Continued			
<i>Effect of chronic exposure to product:</i> Repeated and prolonged skin contact may lead to skin disorders. Long term vapor inhalation can cause kidney damage.			
5-Chloro-2-methyl-2H-isothiazol-3-one 8 hr TWA 0.05 mg/m <sup>3</sup> 2-Methyl-2H-isothiazol-3-one Formaldehyde (formed in solution) (formed in solution) TRK Value: 0.5ppm 8hr TWA 0.62 mg/m <sup>3</sup> OSHA (PELs) Exposure limits	Non Irritating <i>Irritancy of product</i>	Non Sensitizing <i>Sensitization to product</i>	NA <i>Carcinogenicity</i>
NA <i>Teratogenicity</i>	NA <i>Reproductive toxicity</i>	NA <i>Mutagenicity</i>	Toxic to Marine Life <i>Synergistic products</i>

SECTION 7 – PREVENTIVE MEASURES		
Personal protective equipment:		
PVC GLOVES <i>Gloves (specify)</i>	NA <i>Respirator (specify)</i>	SAFETY GOGGLES <i>Eyes (specify)</i>
NA <i>Footwear (specify)</i>	RUBBER APRON <i>Clothing (specify)</i>	Other (specify)
<i>Engineering controls:</i> Local exhaust ventilation is recommended. All equipment must be electrically grounded. Use flameproof equipment and isolate all potential sources of ignition. Isolate electrical ignition sources.		
<i>Leak and spill procedure:</i> Absorb liquid in absorbent clay granules. Spilt product presents a slip hazard.		
<i>Waste disposal:</i> According to government regulations. Dispose through an authorized waste contractor to a licensed site.		
<i>Handling procedures end equipment:</i> Immediately issue NO SMOKING and NO NAKED FLAMES warnings. Isolate electrical ignition sources. Avoid inhaling the vapor and contact with skin and eyes. Avoid sources of ignition.		
<i>Storage requirements:</i> Store in clean, dry conditions in temperatures 5 – 30°C. Keep container closed and ensure label intact and legible. Cover when not in use.		
<i>Shipping information:</i> No Special precautions are necessary. WHMIS CLASSIFICATION: N/A (Not Controlled)		

SECTION 8 – FIRST AID MEASURES
<i>Specific measures:</i>
<b>SKIN:</b> Remove contaminated clothing immediately. Wash well with soap and plenty of water. If irritation develops, seek medical aid immediately. Show the container label
<b>EYES:</b> Flush with clean water immediately for 5 minutes. Seek medical aid.
<b>INHILATION:</b> Remove from exposure, rest and keep warm. Seek medical aid.
<b>INGESTION:</b> <u>DO NOT</u> induce vomiting. Wash mouth with water or milk. Give milk to drink. Beware of aspiration if vomiting occurs. If aspiration (inhalation of liquid into the lungs) is suspected or occurs, get immediate medical help.

SECTION 9 – PREPARATION INFORMATION
e-Black Solutions      Tel: 1-866-878-8886      November 2021, replaces all previous issues
<i>Note:</i> NA: Not Applicable.                      NE: Not Established.

THE INFORMATION CONTAINED HEREIN DERIVES FROM DATA CONSIDERED TO THE BEST OF KNOWLEDGE TO BE ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS OBTAINED FROM THE USE THEREOF.