MATERIAL SAFETY DATA SHEET PAGE 1 SECTION 1 - PRODUCT INFORMATION **Blackfast Chemicals** ++44(0)20 8339 7370 Telephone number Manufacturers name Unit B, 121 Roebuck Road, Chessington, Surrey, UK, KT9 1EU Manufacturers Address Product ID# Product identification: BLACKFAST 551 CONDITIONER 551-25L, 551-4PK, 551-5L, 551-2L, 551-25LU, 551-4PKU, 551-5LU, 551-2LU Product use: Surface preparation of iron and steel Size: 25 litre, 4 pack, 5 litre, 2 litre e-Black Solutions Emergency #: 1-866-878-8886 Suppliers name: Address: 97 Wilkes Street, Brantford, Ontario, Canada N3T 4W2 SECTION 2 – HAZARDOUS INGREDIENTS HAZARDOUS INGREDIENTS % CAS NUMBER LD50 OF INGREDIENT None NA NA NA SECTION 3 - PHYSICAL DATA **Odourless Colorless Liquid** NA Liquid Physical state Odour and appearance Odor threshold NA NA NA 100° C. 0º C. Vapor density Evaporation rate Boiling point Freezing Point Vapor pressure 1.10 @ 20° C 2.5 - 3.0 Complete Specific Gravity Solubility/ Miscibility in water На SECTION 4 - FIRE OR EXPLOSION HAZARD Conditions of Flammability: Not Flammable. Will not support combustion. Means of extinction: NA NA NA NA Flash point and method Upper flammable limit Lower flammable limit NA NA Auto-ignition temperature Hazardous combustion products Sensitivity to mechanical impact: NO Sensitivity to static discharge: NO Explosion Data: SECTION 5 – REACTIVITY DATA Chemical stability: Solution is stable under normal conditions. Incompatibility with other substances: NE Reactivity and under what conditions?: NE Oxides of Carbon, Phosphorus, Nitrogen. Hazardous decomposition products:

SECTION 6 – HEALTH HAZARD DATA (TOXICOLOGICAL PROPERTIES)					
Route of entry: Skin contact, Eye contact.	SKIN: Irritation, EYES: Irritation		S: Irritation		
Effects of acute exposure to the product: NE Effect of chronic exposure to product: NE			duct: NE		
NA	NA	NA	NA		
OSHA (PELs) Exposure limits:	Irritancy of product	Sensitization to product	Carcinogenicity		
NA	NA	NA	NA		
Teratogenicity	Reproductive toxicity	Mutagenicity	Synergistic products		

SECTION 7 – PREVENTIVE MEASURES Personal protective equipment:				
PVC GLOVES Gloves (specify)	NA Respirator (specify)	SAFETY GOGGLES Eyes (specify)		
NA Footwear (specify)	RUBBER APRON Clothing (specify)	Remove contaminated clothing immediately. Other (specify)		

Engineering controls: Local exhaust ventilation is recommended when in continuous use.

Leak and spill procedure: Absorb liquid in absorbent clay granules.

Waste disposal: Disposal must be in accordance with local and national legislation. Dispose through an authorised waste contractor to a licensed site.

Handling procedures end equipment: Avoid inhaling the vapor. Avoid contact with skin and eyes.

Storage requirements: Store in clean, dry conditions. Keep container closed and ensure label intact and legible. Prevent from freezing. Cover when not in use.

Shipping information: No special precautions are necessary. Prevent from freezing.



WHMIS CLASSIFICATION: N/A (Not Controlled)

SECTION 8 - FIRST AID MEASURES

Specific measures:

INHALATION: Remove to fresh air.

INGESTION: Gargle, rinse mouth and drink large amounts of water. Seek medical aid.

SKIN: Remove contaminated clothing. Wash well with plenty of water. If irritation develops, seek medical aid

EYES: In case of contact with eyes, flush immediately with plenty of water for 10 minutes and seek medical aid.

SECTION 9 - PREPARATION INFORMATION

e-Black Solutions Tel: 1-866-878-8886 June 2023, replaces all previous issues

Note: NA: Not Applicable NE: Not Established