BLACKFAST 833C DEWATERING OIL

Page: 1

Creation Date: 2016-06-01

Revision Date: 2023-06-28

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: BLACKFAST 833C DEWATERING OIL / CORROSION INHIBITOR

Product codes: 833C, 833CU, 833C-205L, 833C-205LU

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Use as supplied. PC1: Adhesives, sealants. PC24: Lubricants, greases, release products.

1.3. Details of the supplier of the safety data sheet

Manufacturer:	Cromac Inc.	CAN/USA Reseller: e-Black Solutions
	2828 Slough Street	97 Wilkes Street
	Mississauga	Brantford
	Ontario	Ontario
	L4T 1G3	N3T 4W2
	CANADA	CANADA
Tel:	1-905-458-1999	Tel: 1-866-878-8886
Fax:	1-905-458-7899	Fax: 1-866-290-3642
		Email: certification@e-blacksolutions.com

1.4. Emergency telephone number

Emergency tel: 1-800-424-9300 Chemtrec

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Asp. Tox. 1: H304

Most important adverse effects: May be fatal if swallowed and enters airways.

2.2. Label elements

Label elements:

Hazard statements: H304: May be fatal if swallowed and enters airways.

Hazard pictograms: GHS08: Health hazard

GHS02: Flammable Liquid



BLACKFAST 833C DEWATERING OIL

Page: 2

 Signal words:
 Warning

 Precautionary statements:
 P102: Keep out of reach of children.

 P260:
 Do not breathe spray.

 P262:
 Do not get in eyes, on skin, or on clothing.

 P301+310:
 IF SWALLOWED: Immediately call a POISON CENTER/doctor/.

 P331:
 Do NOT induce vomiting.

2.3. Other hazards

Other hazards: Frequent or prolonged contact may defat and dry the skin, leading to discomfort and

dermatitis.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY - REACH registered number(s): 01-2119486659-16-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-150-3	64742-48-9	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226	>75%

BASEOIL - UNSPECIFIED - DISTILLATES (PETROLEUM), SOLVENT-REFINED HEAVY PARAFFINIC - REACH registered number(s): 01-2119488706-23-XXXX

265-090-8 64741-88-4 · 10-20%

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

BLACKFAST 833C DEWATERING OIL

Page: 3

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool

containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with

skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up

to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal

by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of mists in the air. Avoid direct contact with the substance.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

Suitable packaging: Steel drums. Polyethylene.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

BLACKFAST 833C DEWATERING OIL

Page: 4

Hazardous ingredients:

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

Workplace exposure limits:

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
USA	180	-	-	-

Respirable dust

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area.
Respiratory protection:	Respiratory protection not required.
Hand protection:	Gloves (oil-resistant). Breakthrough time of the glove material > 8 hours.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Protective clothing.
Environmental:	Ensure a retention tank is installed.

Section 9: Physical and chemical properties

9.1. Information on basic physic	al and chemical properties		
State:			
Colour:			
	Solvent.		
Evaporation rate:	No data available.		
Oxidising:	Non-oxidising (by EC criteria)		
Solubility in water:	Insoluble		
Boiling point/range°C:	170 (338F)	Melting point/range°C:	No data available.
Flammability limits %: lower:	1%	upper:	6%
Flash point°C:	40 (104F)	Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available.	Vapour pressure:	No data available.
Relative density:	0.82	pH:	No data available.
VOC g/l:	600		

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

BLACKFAST 833C DEWATERING OIL

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

LOW BOILING POINT HYDROGEN TREATED NAPHTHA - NAPHTHA (PETROLEUM), HYDROTREATED HEAVY

DERMAL	RBT	LD50	2000	mg/kg
ORAL	RAT	LD50	5000	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Aspiration hazard	•	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: No data available.

Section 12: Ecological information

12.1. Toxicity

Eco toxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

BLACKFAST 833C DEWATERING OIL

Page: 6

12.3. Bio accumulative potential

Bio accumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible Eco toxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

 Disposal operations:
 Transfer to a suitable container and arrange for collection by specialised disposal company.

 Waste code number:
 13 08 99

 Disposal of packaging:
 Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

 NB:
 The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EC) No
	1272/2008.
Phrases used in s.2 and s.3:	H226: Flammable liquid and vapour.
	H304: May be fatal if swallowed and enters airways.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive and
	shall be used only as a guide. This company shall not be held liable for any damage resulting
	from handling or from contact with the above product.